



CERTIFIED
PORCELAIN
 TILE

FUSION COTTO™

GLAZED PORCELAIN FLOOR & CERAMIC MOSAIC WITH REVEAL IMAGING®

FLOOR



AMERICAN OLEAN®
 PROVEN IN TILE™

AMERICANOLEAN.COM

FUSION COTTO™

Melding old-world cotto with contemporary concrete, Fusion Cotto's nod to the enviable European look is as relevant to residential interiors as it is to commercial spaces. Reveal Imaging™ enriches its popular tone-on-tone depth of color. Meanwhile, the structured surface also provides texture for increased slip resistance. Popular large-format sizes are available in four distinct colors, and a brick-joint mosaic completes the look. At home on floors and walls, this versatile collection spans both contemporary and traditional spaces with ease.

Photo features Marrone in 18 x 18 on the floor.

FUSION COTTO™

GLAZED PORCELAIN FLOOR & CERAMIC MOSAIC
WITH REVEAL IMAGING®

FIELD TILE



ECRU CF11



GRIGIO CF12



MARRONE CF13



COTTO CF14

2 x 4 GLAZED CERAMIC BRICK-JOINT MOSAIC



ECRU CF11



GRIGIO CF12



MARRONE CF13




COTTO CF14

FUSION COTTO™

GLAZED PORCELAIN FLOOR & CERAMIC MOSAIC WITH REVEAL IMAGING®

SIZES, SHADE VARIATION & PRICING



18 x 18 FIELD TILE
(17-13/16" x 17-13/16")
(45.2 cm x 45.2 cm)



12 x 12 FIELD TILE
(11-13/16" x 11-13/16")
(30 cm x 30 cm)



12 x 24 FIELD TILE
(11-13/16" x 23-13/16")
(30 cm x 60.48 cm)



2 x 4 BRICK-JOINT MOSAIC
(12" x 12")
(30.48 cm x 30.48 cm)



RANDOM
(V4)

TILE THICKNESS: 5/16" (12 x 12, 18 x 18), 3/8" (12 x 24), 1/4" Mosaic
RECOMMENDED GROUT JOINT: 3/16" (when rectangular size is used in a staggered brick-joint pattern, the overlap should not exceed 33%), 1/8" Mosaic
RELATIVE PRICING: Medium to High

PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOH'S	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Field	< 0.5%	> 275 lbs.	8.0	Resistant	CF11 - 4 CF12, CF13, CF14 - 3
Mosaic	< 3.0%	> 250 lbs.	8.0	Resistant	CF11 - 4 CF12, CF13, CF14 - 3

CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

SETTING

- Latex modified thin-set
- Epoxy

GROUTING

- Sanded grout
- Epoxy grout

Cover photo features Fusion Cotto Marrone in 18 x 18 on the floor.

NOTES

SPECIAL INSTALLATION REQUIREMENT:

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.

All or select items within this series are made in the USA. For more information visit www.americanolean.com.



PRE-CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2016 AMERICAN OLEAN (06/16)
ASSEMBLED IN MEXICO



AMERICAN OLEAN®
PROVEN IN TILE™

TRIM



BULLNOSE

S-43C9
3 x 12

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

FLOOR APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	●
Wet & Level - Interior	≥ 0.42	●
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	○
Ramps & Inclines	≥ 0.65	○

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.americanolean.com/dcof.

OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	●
Countertops	●
Pool Linings	●*

APPLICATION NOTES:

* 2 x 4 mosaic only.

Floor tile suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Mosaics suitable for exterior applications in non-freezing climates only when proper installation methods are followed.