



CERTIFIED
PORCELAIN
 TILE
A.P.C. for best water absorption

DANYA™

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC WITH REVEAL IMAGING®

FLOOR
 & WALL



AMERICAN OLEAN®
 PROVEN IN TILE™

AMERICANOLEAN.COM

DANYA™

Rich in both color and visual appeal, Danya captures the essence of fluid movement. Its bold stone visual is coupled with soft striations, giving it an exquisite look reminiscent of ancient riverbeds. An update to traditional stone looks, Danya is ideal for the homeowner with discriminating taste; its performance characteristics and design flair make it attractive to the commercial market as well.




Photo features Danya Riverbed 12 x 12 floor tile in a grid pattern on the floor and 10 x 14 wall tile with 3 x 3 mosaic on the fireplace, also features Color Appeal™ Sable 1 x 1 mosaic on the inside corner of the fireplace.

DANYA™

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC
WITH REVEAL IMAGING®

GLAZED PORCELAIN FLOOR TILE



STREAM DY01



COVE DY02



RIVERBED DY03



BASIN DY04

10 x 14 GLAZED CERAMIC WALL TILE



STREAM DY01



COVE DY02



RIVERBED DY03



BASIN DY04

3 x 3 GLAZED CERAMIC MOSAIC



STREAM DY01



COVE DY02



RIVERBED DY03




BASIN DY04

DANYA™

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC WITH REVEAL IMAGING®

SIZES, SHADE VARIATION & PRICING



18 x 18 FLOOR TILE
(17-13/16" x 17-13/16")
(45.20 cm x 45.20 cm)



12 x 24 FLOOR TILE
(11-13/16" x 23-13/16")
(30.00 cm x 60.48 cm)



12 x 12 FLOOR TILE
(11-13/16" x 11-13/16")
(30.00 cm x 30.00 cm)



10 x 14 WALL TILE □
(9-13/16" x 13-15/16")
(24.99 cm x 35.40 cm)



3 x 3 MOSAIC □■
(12" x 24" Sheet)
(30.48 cm x 60.90 cm Sheet)

- Ceramic body
- Dot-mounted



HIGH
(V3)

TILE THICKNESS: 5/16" Floor & Wall, 1/4" Mosaic
RECOMMENDED GROUT JOINT: 3/16" Floor
 (overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern),
 1/16" Wall, 1/8" Mosaic
RELATIVE PRICING: Medium to Low

PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOHS	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Floor	< 0.5%	> 275 lbs.	8.0	Resistant	4 (DY01, DY02); 3 (DY03, DY04)
Mosaic	< 3.0%	> 250 lbs.	8.0	Resistant	4 (DY01, DY02); 3 (DY03, DY04)
Wall	< 20.0%	> 120-230 lbs.	4.0 - 6.5	Resistant	N/A

CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

SETTING

- Latex modified thin-set
- Epoxy

GROUTING

- Sanded grout for floor & mosaic
- Unsanded grout for wall
- Sanded cement grout for floor & mosaic
- Unsanded cement grout for wall
- Epoxy grout

Cover photo features Danya Riverbed 12 x 12 floor tile in a grid pattern on the floor and 10 x 14 wall tile with 3 x 3 mosaic on the fireplace, also features Color Appeal™ Sable 1 x 1 mosaic on the inside corner of the fireplace.

NOTES

Special consideration must be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

All or select items within this series are made in the USA. For more information visit americanolean.com/MadeInUSA.

For additional information, refer to "Factors to Consider" at americanolean.com/Factors.

TRIM



FLOOR BULLNOSE □
P-43C9
3 x 12



COVE BASE □
S-36C9T
6 x 12




COVE BASE OUTCORNER □
SC-36C9T
6 x 1



WALL BULLNOSE □
S-4310 (10" side)
3 x 10



WALL BULLNOSE CORNER □
SN-4310
3 x 3



QUARTER ROUND □
A1061P2
1 x 6

□ Ceramic body

Floor bullnose, cove base and cove corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

FLOOR APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	●
Wet & Level - Interior	≥ 0.42	●*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	○
Ramps & Inclines	≥ 0.65	○

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	●
Countertops	●**
Pool Linings	●***

APPLICATION NOTES:

* Field tile and mosaic suitable. Mosaic also suitable for residential and light commercial shower floors.

** Does not apply to wall tile

*** Mosaic only

Floor tile suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Wall tile & mosaic suitable for exterior applications in non-freezing climates only when proper installation methods are followed.



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE
©2016 AMERICAN OLEAN (10/16)



AMERICAN OLEAN®
PROVEN IN TILE™

