

CREEKWOOD™

WITH REVEAL IMAGING™

PORCELAIN



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

CREEKWOOD™

Creekwood by American Olean provides the warmth and ambiance of natural wood flooring with the durability of a porcelain tile. The 6 x 36 size allows for traditional wood-plank installations in settings that demand higher performance and functionality than wood provides. With slight undulations, linear wood grains, and realistic 'knots', Creekwood utilizes Reveal Imaging™ to create an authentic wood look on a porcelain body.



Photo features Ash River in 6 x 36 on floor.

FLOOR TILE



BIRCH STREAM CW96



MAPLE LAKE CW97




ASH RIVER CW99



WALNUT BROOK CW98

SIZES, SHADE VARIATION & PRICING



6 x 36 FLOOR TILE
(5-7/8" x 35-7/16")
(15 cm x 90 cm)



HIGH
(V3)

TILE THICKNESS: 5/16"
RECOMMENDED GROUT JOINT: 3/16" (when rectangular size is used in a staggered brick-joint pattern, the overlap should not exceed 33%)
RELATIVE PRICING: Medium

TRIM



BULLNOSE
S-43H9
3 x 18

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

FLOOR APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	<input checked="" type="radio"/>
Wet & Level - Interior	≥ 0.42	<input checked="" type="radio"/>
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	<input type="radio"/>
Ramps & Inclines	≥ 0.65	<input type="radio"/>

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.americanolean.com/dcof.

OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	<input checked="" type="radio"/>
Countertops	<input checked="" type="radio"/>
Pool Linings	<input type="radio"/>

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOH'S	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Floor	< 0.5%	> 275 lbs.	8.0	Resistant	3

CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

SETTING

- Latex modified thin-set
- Epoxy

GROUTING

- Sanded grout
- Sanded cement grout
- Epoxy grout

NOTES

SPECIAL INSTALLATION REQUIREMENT: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20 x 20, large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.



PRE CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2015 AMERICAN OLEAN (03/15)
ASSEMBLED IN MEXICO



AMERICAN OLEAN®
PROVEN IN TILE™