

COLORBODY PORCELAIN STONEWARE

TRUEDGE™ | REVEAL IMAGING™





CLASSENTINO MARBLE



CLASSENTINO MARBLE" offers the bold, realistic look of marble in a porcelain tile. The intricacies and veining of natural marble are artfully reproduced via Marazzi's Reveal Imaging® technology. The collection is offered in five colors, as well as two different finishes, perfect for any design style. Classic weave and linear hex mosaics accent the collection for a modern twist on these timeless materials that make a profound statement on floors and walls in both residential and commercial spaces.





ASSENTINO MARBL

COLORBODY™ PORCELAIN STONEWARE

TRUEDGE™ | REVEAL IMAGING®

FLOOR TILE - AVAILABLE IN MATTE AND POLISHED



CT30 Palazzo White



CT31 Corinth Beige



CT32 Coliseum Gray



CT33 Imperial Brown



CT34 Centurio Black

2 x 3 LINEAR HEX MOSAIC - MATTE 12 x 12 SHEET



CT30 Palazzo White CT31 Corinth Beige





CT32 Coliseum Gray



CT33 Imperial Brown CT34 Centurio Black



CLASSIC WEAVE MOSAIC - POLISHED 14 x 14.5 SHEET



CT35 Coliseum Gray & Palazzo White



CT36 Palazzo White & Centurio Black



CT37 Corinth Beige & Imperial Brown

USAGE

Floors	Walls	Countertops
F	W	С

CLASSENTINO MARBLE

COLORBODY™ PORCELAIN STONEWARE

TRUEDGE™ | REVEAL IMAGING®

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
24 x 48 Floor Tile	(23-3/8" x 46-15/16") (59.44 cm x 119.2 cm)	3/8"	15.26	2
24 x 24 Floor Tile	(23-3/8" x 23-3/8") (59.44 cm x 59.44 cm)	3/8"	15.20	4
12 x 24 Floor Tile	(11-5/8" x 23-3/8") (29.56 cm x 59.44 cm)	3/8"	15.12	8
2 x 3 Linear Hex Mosaic* (Mesh- Mounted)	(12-1/8" × 12-3/16") (30.81 cm × 30.94 cm)	3/8"	8.50	10
Classic Weave Mosaic† (Mesh- Mounted)	(14-3/8"x14-9/16") (36.49 cm x 37.06 cm)	3/8"	10.50	10

^{*}Only available in Matte

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	•
Wet & Level - Interior Floor	≥ 0.42	■ †
Shower Floors (Residential or Light Commercial)	≥ 0.42	*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	*

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest", visit marazzitile.com/DCOF.

APPLICATION NOTES:

Mosaics and floor tile are suitable for many residential and commercial floors; in addition, mosaics are also suitable for residential and light commercial shower floors. Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

* Linear Hex Mosaic only † Matte Finish only



Floor Tile



Wall Tile



TruEdge™



Reveal Imaging®





All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

TRIM

Description	Number	Size	Shape
Floor Bullnose	S-43F9	3 x 24	

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Random Variation (V4)

*Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

PERFORMANCE CHARACTERISTICS

	ASTM#	Matte Result	Polished Result
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C648	> 275 lbs	> 275 lbs
Scratch Hardness	MOHS	8.0	7.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

[†]Only available in Polished



COVER FEATURES CLASSENTINO MARBLE™ IN:
PALAZZO WHITE - POLISHED
LINEAR HEX MOSAIC - COLISEUM GRAY MATTE
CLASSIC WEAVE MOSAIC - COLISEUM GRAY & PALAZZO WHITE POLISHED

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with Marazzi Customer Service for details.