

# SERENTINA™

GLASS & STONE MOSAIC

MOSAIC



AMERICAN OLEAN®  
PROVEN IN TILE™

AMERICANOLEAN.COM

# SERENTINA™

Crafted with eye-catching glass and stone, Serentina by American Olean® puts luxurious style within reach. Featuring striking geometric designs in three versatile patterns and six unique color blends, the collection offers flexibility to perfectly accent residential spaces. Ideal for backsplashes or tub and shower surrounds, Serentina can also be used as borders or liners to add a subtle touch of elegance.

Photo features Serentina Zen herringbone mosaic on backsplash.

# SERENTINA™

GLASS & STONE MOSAIC

## HERRINGBONE

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97



SOLITUDE SA98

## BLOCK RANDOM

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97



SOLITUDE SA98

## RANDOM INTERLOCKING

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97



SOLITUDE SA98

# SERENTINA™


GLASS & STONE MOSAIC

## SIZES, SHADE VARIATION & PRICING




**HERRINGBONE  
GLASS & STONE MOSAIC ■**  
(11-1/2" x 12-3/4" Sheet)  
(29.21 cm x 32.39 cm Sheet)

■ Mesh-mounted



**BLOCK RANDOM  
GLASS & STONE MOSAIC ■**  
(12-1/4" x 11-7/8" Sheet)  
(31.12 cm x 31.18 cm Sheet)



**RANDOM INTERLOCKING  
GLASS & STONE MOSAIC ■**  
(13-1/4" x 11-3/4" Sheet)  
(33.66 cm x 29.85 cm Sheet)



**RANDOM  
(V4)**

**TILE THICKNESS:** 1/4"  
**RECOMMENDED GROUT JOINT:** 1/8"  
**RELATIVE PRICING:** Low to Medium

## PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOHS	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Mosaic	< 0.5%	> 100 lbs.	4.0	Resistant	4

Cover photo features Zen herringbone mosaic on backsplash and Theoretical™ Logical Gray 12 x 24 field tile on the floor.

## NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information, refer to "Factors to Consider" at [americanolean.com/Factors](http://americanolean.com/Factors)

## APPLICATIONS

	SUITABLE
Walls/Backsplashes	<input checked="" type="radio"/>
Countertops	<input type="radio"/>
Pool Linings	<input type="radio"/>

### APPLICATION NOTES:

Suitable for exterior wall applications in freezing and non-freezing climates when proper installation methods are followed.

### CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

### SETTING

- Latex modified thin-set
- Epoxy

### INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

### GROUTING

- Unsanded grout
- Epoxy grout



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2017 AMERICAN OLEAN (02/17)



AMERICAN OLEAN®  
PROVEN IN TILE™